Technical Datasheet



PEKA-Fix 600 SE

Art.-Nr.: 136089



This double-sided tape consists of a special cloth carrier layered on both sides with a **Description:**

modified dispersion acrylate adhesive. The adhesive is resistant to aging and plasticiser and is exceptional for its flame resistance and self-extinguishing qualities. This special

textile tape is lined with a white double-sided silicone paper.

Area of use: This double sided tape is used especially in the nautical and aeronautical industries.

Remark: Tested according to ATS 1000.001 and FAR 25.853 App. F.



Technical Datasheet 28-05-2018



PEKA-Fix 600 SE

Art.-Nr.: 136089

Technical Data:

Category	Double-sided adhesive cloth tapes
Carrier	Woven polyamide
Thickness	0,28 mm
Adhesive	Modified dispersion acrylate
Liner	Silicone coated paper on both sides, 90 g/m², white
Adhesive power (FINAT TM 1, on stainless steel)	after 1 min 14 N/25 mm after 20 min 16 N/25 mm after 24 h 18 N/25 mm
Shear strength (FINAT TM 8, on stainless steel)	4 h at 23 °C
Temperature resistance 1h	-40 °C to 100 °C
Application temperature	> 15 °C
Shelf life	2 years in original packaging, at 20 $^{\circ}\mathrm{C}$ and 50 $^{\circ}\mathrm{C}$ relative humidity

