Technical Datasheet 10-07-2018



PEKA-Mount 7401

Art.-Nr.: 183189



Description:

This mounting tape consists of a white, closed-cell polyethylene foam coated on both sides with a rubber adhesive. The rubber adhesive adheres well among other things on apolar substrates. The double-sided mounting tape is lined with a white silicone paper

Area of use:

For fixing of boards, displays and for a variety of household applications. A universal, economical product. Good adhesion also on rough surfaces.



Technical Datasheet 10-07-2018



PEKA-Mount 7401

Art.-Nr.: 183189

Technical Data:

| Category | Double-sided adhesive foam tapes |
|---|--|
| Carrier | Closed-cell polyethylene foam, white, 1000 micron |
| Density | 58 kg/m ³ |
| Thickness | 1,10 mm |
| Adhesive | Rubber |
| Liner | White paper, both sides coated with silicone, 90 g/m² |
| Adhesive power (FINAT TM 1, on stainless steel) | after 1 min 18 N/25 mm after 20 min > 18 N/25 mm after 24 h > 18 N/25 mm |
| Shear strength (FINAT TM 8, on stainless steel) | > 500 hours at 23 °C $$ 1 hour at 70 °C |
| LoopTack (FINAT TM 9) | 35 N/25 mm |
| Temperature resistance 1h | -30 °C to 70 °C |
| Temperature resistance (S.A.F.T.) | 75 ℃ |
| Application temperature | > 15 °C |
| Shelf life | 1 year in original packaging, at 20 $^{\circ}\mathrm{C}$ and 50 $\%$ relative humidity |

