Technical Datasheet

27-06-2019



PEKA-Fix 1202 Verlegegitter, beiseitig schwachhaftend

Art.-Nr.: 120273



Description:

Adhesion characteristics of this solvent-free acrylic glue system guarantees safe functionality for fixing of floors. The pressure-sensitive adhesive is characterized by a high degree of condensation-, aging- and plasticizer resistance. Covered is the glass fibre adhesive mesh with a about standing transparent PE foil.

Area of use:

PEKA-Fix 1202 is a low tack bonded glass fibre adhesive mesh and is used for dry and complete fixing of standard floor coverings. Commonly used flooring backs can be applied for most surfaces with good absorbing capacity.

Note:

Not suitable for marble floors.



Technical Datasheet

27-06-2019



PEKA-Fix 1202 Verlegegitter, beiseitig schwachhaftend

Art.-Nr.: 120273

Technical Data:

Category	Double-sided adhesive cloth tapes
Carrier	Glass fiber fabric
Thickness	0,28 mm - 0,30 mm (ohne Liner)
Adhesive	Acrylic dispersion
Liner	PE film, transparent
Temperature resistance 1h	-30 °C to 80 °C
Application temperature	5 °C to 30 °C
Peel adhesion	ca. 1 N/50 mm (DIN EN 1939)
Shear adhesion	100 g/625 mm² (DIN EN 1943)

