

PEKA-Fix 632

Art.-Nr.: 134373



Description:

Area of use:

PEKA Stanz- und Klebtechnik GmbH & Co. KG · Am Forst 30 · D-74889 Sinsheim
Tel.: +49 (0) 72 65 91 30-0 · FAX: +49 (0) 72 65 91 30-35 · peka-stanztechnik.local · info@peka-stanztechnik.local

The specifications have been determined by standard test methods and are average values. Due to the variety of uses of the PEKA products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

Technical Datasheet

17-02-2022

PEKA-Fix 632

Art.-Nr.: 134373



Technical Data:

Category	Double-sided adhesive tapes with film carrier
Carrier	
Thickness	0,17 mm
Adhesive	
Liner	
Temperature resistance 1h	
Tensile strength	Quer: 200 N/mm ² Längs: 200 N/mm ²
Elongation at tear	Quer: 110 % Längs: 110 %
Peel strength - AFERA 4001 P11	Abgedeckte Seite: 30 N/25 mm Offene Seite: 6 N/25 mm

PEKA Stanz- und Klebetechnik GmbH & Co. KG · Am Forst 30 · D-74889 Sinsheim

Tel.: +49 (0) 72 65 91 30-0 · FAX: +49 (0) 72 65 91 30-35 · [peka-stanztechnik.local](mailto:info@peka-stanztechnik.local) · info@peka-stanztechnik.local

The specifications have been determined by standard test methods and are average values. Due to the variety of uses of the PEKA products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

