

## PEKA-Fix 3125

Art.-Nr.: 139289



### Description:

This double-sided tape consists of a hard PVC film carrier, layered on both sides with a modified solvent acrylate adhesive. It has a very good resistance against UV radiation, extreme temperatures, chemicals, solvents and humidity. Its highly shearresistant adhesive has excellent durability when attached to metal, varnish and high energy surfaces. It has a good adhesive durability when attached to low energy surfaces. Because of its high adhesive mass it is also appropriate for rough or structured surfaces.

### Area of use:

Used for the secure attachment of truck and car mirrors in plastic housings. Used as an adhesive medium for signs as well as for extruded synthetic profiles and for durable installation in the furniture industry. Used for the attachment of trims, bars and laminates to a variety of surfaces. For the fixing of covers and handles in the audio, household appliance and electrical industry.

PEKA Stanz- und Klebtechnik GmbH & Co. KG · Am Forst 30 · D-74889 Sinsheim  
Tel.: +49 (0) 72 65 91 30-0 · FAX: +49 (0) 72 65 91 30-35 · [www.peka-stanztechnik.de](http://www.peka-stanztechnik.de) · [info@peka-stanztechnik.de](mailto:info@peka-stanztechnik.de)

The specifications have been determined by standard test methods and are average values. Due to the variety of uses of the PEKA products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

## PEKA-Fix 3125

Art.-Nr.: 139289

### Technical Data:

<b>Category</b>	Double-sided adhesive tapes with film carrier
<b>Carrier</b>	Hard PVC film, white, 38 micron
<b>Thickness</b>	0,26 mm
<b>Adhesive</b>	Modified solvent acrylate
<b>Liner</b>	Brown paper, 90 g/m <sup>2</sup> , both sides coated with silicone
<b>Adhesive power (FINAT TM 1, on stainless steel)</b>	after 1 min 32 N/25 mm   after 20 min 36 N/25 mm   after 24 h 38 N/25 mm
<b>Shear strength (FINAT TM 8, on stainless steel)</b>	> 400 h at 23 °C   > 6 h at 70 °C
<b>LoopTack (FINAT TM 9)</b>	23 N/25 mm
<b>Temperature resistance 1h</b>	-40 °C to 70 °C
<b>Temperature resistance (S.A.F.T.)</b>	100 °C
<b>Application temperature</b>	> 15 °C
<b>Shelf life</b>	2 years in original packaging, at 20 °C and 50 % relative humidity
<b>Resistance to solvents and chemicals</b>	With expert application resistant to most oils, grease, fuels, aliphatic solvents, weak acids, salts and alkalis