Technical Datasheet



PEKA-Fix 6089 H

Art.-Nr.: 146089



This double-sided tape consists of a rayon carrier layered on both sides with a rubber **Description:**

adhesive. It is exceptional through its high transparency and aging resistance. The

adhesive is lined with a double-sided silicone paper.

Area of use: This double-sided tape is highly rip-resistant and very suitable for the installation of

carpets. This high quality carpet tape has an excellent colour stability and is therefore

less likely to stain more sensitive floor surfaces.

Remark: Not appropriate for artificial stone floors, marble or floor materials with a high

plasticiser content.



Technical Datasheet



PEKA-Fix 6089 H

Art.-Nr.: 146089

Technical Data:

Category	Double-sided adhesive cloth tapes
Carrier	Rayon
Thickness	0,24 mm
Adhesive	Rubber
Liner	Silicone coated paper on both sides, 80 g/m², brown
Adhesive power (FINAT TM 1, on stainless steel)	after 1 min 30 N/25 mm after 20 min 32 N/25 mm after 24 h 35 N/25 mm
Shear strength (FINAT TM 8, on stainless steel)	20 h at 23 °C
Temperature resistance 1h	-20 °C to 70 °C
Application temperature	> 15 °C
Shelf life	1 year in original packaging, at 20 °C and 50 % relative humidity

