

Orabond 1489

Art.-Nr.: 148989



Description:

The double-sided adhesive tape, based on a glass fibre scrim, is coated on both sides with a specialised rubber adhesive. The adhesive has a high tack and good resistance to aging. It is lined with a double-sided siliconised paper.

Area of use:

Because of its high rip-resistance and low elongation the adhesive tape is appropriate for stabilizing rubber profiles and sealing tapes, especially on EPDM-based profiles.

Remark:

Limited consistency in the presence of chemicals inclined to migrate (plasticisers).

Orabond 1489

Art.-Nr.: 148989

Technical Data:

Category	Double-sided adhesive cloth tapes
Carrier	Glass fibre scrim
Thickness	0,25 mm
Adhesive	Synthetic rubber
Liner	Brown paper, both sides coated with silicone, 90 g/m ²
Adhesive power (FINAT TM 1, on stainless steel)	after 1 min 35 N/25 mm after 20 min 40 N/25 mm after 24 h 45 N/25 mm
Shear strength (FINAT TM 8, on stainless steel)	24 h at 23 °C 10 min at 70 °C
LoopTack (FINAT TM 9)	56 N/25 mm
Temperature resistance 1h	-40 °C to 100 °C
Temperature resistance (S.A.F.T.)	70 °C
Application temperature	> 15 °C
Shelf life	1 year in original packaging, at 20 °C and 50 % relative humidity