

## PEKA-Mount 726 PP

Art.-Nr.: 181389



**Description:**

This tape consists of white, closed-cell polyethylene foam coated on both sides with a modified solvent acrylate adhesive. This modified solvent acrylate adhesive possesses a high initial adhesion and high shear strength.

**Area of use:**

For the installation of smooth spray cast and extruded plastic parts such as panels, bars and signs, as well as Plexiglas mirrors for interior fit-outs and displays. For use as an adhesive medium for hooks, holders and dispensers on smooth surfaces. Due to good UV, water and age resistance, this product is also suitable for external applications.

**Remark:**

Design qualification and type approval of PV-modules in accordance with IEC 61215. The tape is certified according to UL 746C.

## PEKA-Mount 726 PP

Art.-Nr.: 181389

### Technical Data:

<b>Category</b>	Double-sided adhesive foam tapes
<b>Carrier</b>	Closed-cell polyethylene foam, white, 1000 micron
<b>Density</b>	55 kg/m <sup>3</sup>
<b>Thickness</b>	1,10 mm
<b>Adhesive</b>	Modified solvent acrylate
<b>Liner</b>	PP-film, yellow, both sides coated with silicone, 100 micron
<b>Adhesive power (FINAT TM 1, on stainless steel)</b>	after 1 min > 17 N/25 mm   after 20 min > 18 N/25 mm, tear   after 24 h > 18 N/25 mm, tear
<b>Shear strength (FINAT TM 8, on stainless steel)</b>	> 300 hours at 23 °C   > 3 hours at 70 °C
<b>Temperature resistance 1h</b>	-40 °C to 100 °C
<b>Application temperature</b>	> 15 °C
<b>Shelf life</b>	2 years in original packaging, at 20 °C and 50 % relative humidity