

PEKA-Krepp 6414 Flachkrepp

Art.-Nr.: 641412



Description: General purpose masking tape.

Area of use: General purpose masking tape, suitable for all kinds of simple painting jobs. Tape must be applied at room temperature. Recommended to remove within 36 hours.

Benefits:

- Resistant to most common paints
- Easy removal without adhesive residue
- Good adhesion even on irregular surfaces
- Well conformable to most shapes
- Compatible with most common paints and lacquers
- Removable without breaking
- Hand tearable

PEKA Stanz- und Klebtechnik GmbH & Co. KG · Am Forst 30 · D-74889 Sinsheim
Tel.: +49 (0) 72 65 91 30-0 · FAX: +49 (0) 72 65 91 30-35 · www.peka-stanztechnik.de · info@peka-stanztechnik.de

The specifications have been determined by standard test methods and are average values. Due to the variety of uses of the PEKA products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

PEKA-Krepp 6414 Flachkrepp

Art.-Nr.: 641412

Technical Data:

Category	Single-sided adhesive paper tapes for protecting, covering and for painting work
Carrier	Natural saturated crepe paper, 58 g/m ²
Colours	White
Thickness	0,12 mm
Adhesive	Natural rubber and resins solvent based
Adhesive power on steel N/25 mm	4 N/25 mm
Temperature resistance 1h	60 °C (30 min)
Tensile strength	85 N/25 mm
Shelf life	12 months; suggested storage temperature shall range from 15 °C to 25 °C with max. relative humidity of 65 %. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well.
Elongation at break	7,5 %