


PEKA 3210 PIB-Band

Art.-Nr.: 692539



Description:

It is a self-amalgamating, insulating mastic for insulating and sealing all types of overhead and direct buried electrical connections. It has super adhesion, anti-corrosion and UV resistant characteristics. For high voltage cable ends water sealing with continuous operating temperature up to 90 °C. It is suitable for insulating protection of cable connection up to 1000 V jacketed with vinyl tape. It is also suitable for cable joints, tube and cable ends.

Area of use:

For insulating and protecting all types of low voltage connections and devices, overhead connections, duct seals and cable end seal.

Remark:

- Superior adhesion to metal, and all types of cable insulation and jacket
- Excellent thermal stability
- Impervious to water, salt water, soil and corrosive chemicals

PEKA Stanz- und Klebtechnik GmbH & Co. KG · Am Forst 30 · D-74889 Sinsheim
Tel.: +49 (0) 72 65 91 30-0 · FAX: +49 (0) 72 65 91 30-35 · www.peka-stanztechnik.de · info@peka-stanztechnik.de

The specifications have been determined by standard test methods and are average values. Due to the variety of uses of the PEKA products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

PEKA 3210 PIB-Band

Art.-Nr.: 692539

Technical Data:

Category	Special adhesive tapes
Carrier	Polyisobutylene
Colours	Black
Thickness	0,50 mm
Temperature resistance 1h	90 °C
Voltage Resistance	19 kV/mm
Elongation	> 600 %
Water absorption	0,56 %
Dielectric constant	3,2