

PEKA-Mount 7193

Art.-Nr.: 725289



Description:

This mounting tape consists of a white, closed-cell polyethylene foam, which is coated on the covered side with a removable, modified polyacrylate adhesive. The modified acrylate adhesive on the covered side allows easy and residue-less removal from many surfaces. To insure an easy release the covered side is equipped with a PETinterlayer. The open side of the mounting tape is coated with a modified polyacrylate adhesive. Its highly shear-resistant adhesive has a very high tack and an excellent durability when attached to metal, varnish and high-energy plastic surfaces as well as very good adhesion to low energy surfaces.

Area of use:

Universally usable tape for the mounting of a variety of different components, if a subsequent clean removal from one of the materials is necessary.

PEKA Stanz- und Klebtechnik GmbH & Co. KG · Am Forst 30 · D-74889 Sinsheim
Tel.: +49 (0) 72 65 91 30-0 · FAX: +49 (0) 72 65 91 30-35 · www.peka-stanztechnik.de · info@peka-stanztechnik.de

The specifications have been determined by standard test methods and are average values. Due to the variety of uses of the PEKA products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

PEKA-Mount 7193

Art.-Nr.: 725289

Technical Data:

Category	Double-sided adhesive foam tapes
Carrier	Closed-cell polyethylene foam Interlayer: polyester film
Thickness	1,20 mm
Adhesive	Polyacrylate adhesives
Liner	White paper, both sides coated with silicone, 90 g/m ²
Adhesive power (FINAT TM 1, on stainless steel)	Covered side: after 1 min 4 N/25 mm after 20 min 5 N/25 mm after 24 h 6 N/25 mm Open side: after 1 min 17 N/25 mm after 20 min > 18 N/25 mm after 24 h > 18 N/25 mm
Shear strength (FINAT TM 8, on stainless steel)	Covered side: > 300 hours at 23 °C > 72 hours at 70 °C Open side: > 400 hours at 23 °C 6 hours at 70 °C
Temperature resistance 1h	-40 °C to 80 °C
Application temperature	> 15 °C
Shelf life	2 years in original packaging, at 20 °C and 50 % relative humidity