



## Technical Datasheet

27-08-2019

### PEKA-Mount 7115

Art.-Nr.: 740889

#### Description:

This tape consists of a white, closed-cell polyethylene foam coated on both sides with a solvent pure acrylate adhesive. The adhesive guarantees a high final strength and is resistant to extreme temperatures, acids, leaches and solvents. It is inert towards different lacquers for mirrors. The adhesive is lined with a blue paper coated on both sides with silicone and polyethylene.

#### Area of use:

For installation of mirrors in the furniture and sanitary industry. The recommended amount of applied adhesive per 1 kg mirror weight is 60 cm<sup>2</sup>. For adhesion of aluminium, steel and GRP outer skins during the construction of truck containers. For fixing of type and capacity signs as well as displays and product prototypes in the advertising industry. For fixing of panels and handles in the appliance and electrical industry. Ideal for use in exhibitions, conferences and interior fit-outs.

#### Remark:

PEKA-Mount 7115 is the thicker version of the standard adhesive tape PEKA-Mount 7100.



## PEKA-Mount 7115

Art.-Nr.: 740889

### Technical Data:

<b>Category</b>	Double-sided adhesive foam tapes
<b>Carrier</b>	Closed-cell polyethylene foam
<b>Density</b>	67 kg/m <sup>3</sup>
<b>Thickness</b>	1,60 mm
<b>Adhesive</b>	Solvent pure acrylate
<b>Liner</b>	Blue paper, 140 g/m, both sides coated with silicone and polyethylene
<b>Adhesive power (FINAT TM 1, on stainless steel)</b>	after 1 min 16 N/25 mm   after 20 min > 16 N/25 mm, tear   after 24 h > 16 N/25 mm, tear
<b>Shear strength (FINAT TM 8, on stainless steel)</b>	> 1000 hours at 23 °C   > 72 hours at 70 °C
<b>Temperature resistance 1h</b>	-40 °C to 90 °C
<b>Application temperature</b>	> 18 °C
<b>Shelf life</b>	2 years in original packaging, at 20 °C and 50 % relative humidity